

TECHNICAL SPECIFICATIONS

NETPRO-11S 3 KVA ONLINE UPS

Uninterruptible power supply power 3000 V/A:

- 1) Uninterruptible power supply power = 3000 V/A
- 2) Voltage range without battery operation = 230 AC nominal (110-300 volts AC varying depending on output load)
- 3) Input frequency range = 47.5-63 (Hz) (with auto sensitivity)
- 4) Output voltage = 230
- 5) Output rosette = 6 x IEC320
- 6) Type of accumulators = With adjustable valves, lead-acid type choke
- 7) Accumulators Quantity x Voltage x amperage = 6 x 12V x 9.0 amp/hr
- 8) Charging time = 4 hours at 90%
- 9) Accumulators duration of work at full load = 10 min.
- 10) Working temperature = 0°C to +40°C
- 11) Noise level from 1 meter = 50 dBA
- 12) Compliance with standards = EN 62040-1, EN 62040-2, EN 62040-3
- 13) Power factor = 0,95
- 14) Display - liquid crystal display
- 15) Communication interfaces = USB, RS232
- 16) Warranty = 2 years
- 17) Additional functions/features with frequency conversion capability,



AUTOMATIC AND MANUAL BYPASS connection with the possibility of ECO-mode, On-Line technology, compatible software and web browser with remote monitoring function.